

2DC3R53KE-TFD

HCFC, R-22, 60 Hz, 3 - Phase, 460 V , [Also Available with Variable Frequency Drives](#)

Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Copeland Representative for international availability.

Summary

Performance		
Evaporator Temp. (°F)	45.00	35
Condensing Temp. (°F)	130.00	105
Return Gas Temp. (°F)	65.00	55
Liquid Temp. (°F)	115.00	90
Capacity (BTU/hr)	62500	60000
Power (W):	5200	4050
Current (Amps):	8.1	6.8
EER(BTU/Wh):	12.1	14.8
Mass Flow (lbs/hr):	920	800
Sound Data @		
Sound Power (dBA):	0 Avg	0 Max
Vibration mils(peak-peak):	0.0 Avg	5.9 Max
Record Date:	2007-06-08	
Mechanical		
Displacement (in^3/Rev):	11.78	
Displacement (ft^3/Hr):		
Overall Length (in):	23.60	
Overall Width (in):	15.40	
Overall Height (in):	18.60	
Mounting Length (in):	11.60	
Mounting Width (in):	11.00	
Mounting Height (in):	20.10	

Suction Size (in),Type:	1 3 / 8 Sweat
Discharge Size (in),Type:	7 / 8 Sweat
Initial Oil Charge (oz):	80
Oil Recharge (oz):	72
Oil Type:	POE
Net Weight (lbs):	309.0

Internal Free Volume (in^3):

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

Electrical

LRA High* (Amps):	60
LRA Low*(Amps):	
LRA Half Winding (Amps):	
MCC (Amps):	14.6
Max Operating Current (Amps):	
RLA, MCC/1.4(use for contactor selection)(Amps):	10.4
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	9.4
RPM:	1750
Box IP :	
UL File No:	SA-2337
UL File Date:	1988-07-13

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Capacitors

Type	Part No	Low MFD	High MFD	Volts	User Description
------	---------	---------	----------	-------	------------------

No data available in table

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
R-22 HCFC	380/420	3	50	Air Conditioning
R-22 HCFC	380/420	3	50	Medium Temp, Low Condensing
R-22 HCFC	460	3	60	Medium Temp, Low Condensing

Refrigerant	Voltage	Phase	Frequency	Application
R-404A HFC	460	3	60	Medium Temp, Low Condensing
R-404A HFC	380/420	3	50	Medium Temp, Low Condensing
R-407A HFC	460	3	60	Air Conditioning
R-407A HFC	380/420	3	50	Air Conditioning
R-407A HFC	380/420	3	50	Medium Temp, Low Condensing
R-407A HFC	460	3	60	Medium Temp, Low Condensing
R-407C HFC	460	3	60	Air Conditioning

Service Parts

Service Parts				
Reference	Component	Quantity	Description	Comment
99	003-0020-02	1	PLATE-MUFFLER	
99	003-0099-00	1	PLATE-BOTTOM	
99	005-0163-00	1	COVER-TERMINAL BOX	
99	020-0003-28	1	GASKET-O-RING	SENTRONIC SENSOR O-RING GASKET
99	020-0104-00	1	GASKET-HOUSING COVER	
99	020-0146-00	1	GASKET-TERM MTG PLATE	
99	020-0297-13	1	GASKET-SENTRONIC SENSOR	
99	020-0489-00	1	GASKET-DISCH COVER PLATE	SUCTION
99	020-0678-00	1	GASKET-CLOSURE PLATE	
99	020-0709-00	1	GASKET-STATOR COVER	

Accessories

Accessories		
Category	Part Number	Description
Electrical Components	085-0160-00	3 Phase Voltage Monitor. For use with all Copeland 3 Phase Compressors. Consult model family nomenclature for electrical definition in the model number.
Miscellaneous	998-AB52-01	Akylbenzene Oil. Approved for use with specific Copeland Semi Hermetic After Market Compressors. Consult model family nomenclatures for oil identifier in the model number.
Digital Components	023-0039-01	Coil, 120V, Alco - Demand cooling valve (Unloader Valve)
Digital Components	023-0039-02	Coil, 240V, Alco - Demand cooling valve (Unloader Valve)
Demand Cooling	085-0110-00	Control Module 120V 50/60 Hz - Demand Cooling

Category	Part Number	Description
Demand Cooling	085-0110-01	Control Module 240V 50/60 Hz - Demand Cooling
Mounting	998-0700-09	Control Mounting Bracket Kit
(1) Variable Frequency Drive	EVH-322011-R21BEN	Copeland EVH VFD , 3 HP, 230 VAC, 3Ø, 11A, With DC link Choke & Add on EMI filter, Removeable LCD Display, IP21, BACnet/Modbus
(1) Variable Frequency Drive	EVH-322011-R54BDB	Copeland EVH VFD , 3 HP, 230 VAC, 3Ø, 11A, With DC link Choke (Standard EVH), Removeable LCD Display, IP54, BACnet/Modbus
(1) Variable Frequency Drive	EVH-344012-R54BDB	Copeland EVH VFD , 3 HP, 400 VAC, 3Ø, 11A, With DC link Choke (Standard EVH), Removeable LCD Display, IP54, BACnet/Modbus

Electrical Components

Electrical Components

Nomenclature

2DC3R53KE-TFD
FAMILY 2D: 2 Cylinders Discus
DISPLACEMENT C: Standard Valve Plate
MODEL VARIATIONS 3: Standard (Discus II)
PRIMARY APPLICATION RANGE R: ARI High Temp, Rated @ 45/130
NOMINAL CAPACITY AT RATING CONDITION 53: Capacity
CAPACITY MULTIPLIER K: 1000*Capacity
OIL TYPE E: POE Oil
COMPRESSOR MOTOR TYPE T: GENERAL : 3 LEAD SINGLE VOLTAGE, 6 LEAD PART WINDING (575 VOLT), 9 LEAD DUAL VOLTAGE
COMPRESSOR MOTOR PROTECTION F: INTERNAL INHERENT PROTECTION-ONE PROTECTOR USE WITH CONTACTOR

ELECTRICAL CODES

D: 460-60hz-3ph 380/400-50hz-3ph

Miscellaneous

Alternate Application				
Refrigerant	Freq	Phase	Voltage	Application
CFC R-502	60	3 Ø	460 V	R2 MT
CFC R-502	50	3 Ø	380/420 V	R2 MT
HCFC R-22	60	3 Ø	460 V	R2 MD
HCFC R-22	50	3 Ø	380/420 V	R1 AC
HCFC R-22	50	3 Ø	380/420 V	R2 MD
HFC R-407A	60	3 Ø	460 V	R1 AC
HFC R-407A	60	3 Ø	460 V	R2 MD
HFC R-407A	50	3 Ø	380/420 V	R1 AC
HFC R-407A	50	3 Ø	380/420 V	R2 MD
HFC R-404A	60	3 Ø	460 V	R2 MD
Nomenclature				
2DC3R53KE-TFD				

Bill-of-Materials

2DC3R53KE-TFD - BILL OF MATERIALS	
100 - Common U.S. OEM Bill Of Materials	
Suction Connection	Sweat
Suction Size	1 3/8"
Discharge Connection	Sweat
Discharge Size	7/8"
Electrical Connection	
Mounting Assembly	Not Available
Sight Glass	

Crankcase Heater
Schrader Valve
Tandem Ready
Module Voltage
Reference Drawing

1C0 - Common U.S. OEM Bill Of Materials

Suction Connection	Sweat
Suction Size	1 3/8"
Discharge Connection	Sweat
Discharge Size	7/8"
Electrical Connection	
Mounting Assembly	Not Available
Sight Glass	
Crankcase Heater	
Schrader Valve	
Tandem Ready	
Module Voltage	
Reference Drawing	

200 - Common U.S. OEM Bill Of Materials

Suction Connection	Stub
Suction Size	1 3/8"
Discharge Connection	Stub
Discharge Size	1 1/8"
Electrical Connection	Terminal Block
Mounting Assembly	Available
Sight Glass	
Crankcase Heater	
Schrader Valve	
Tandem Ready	
Module Voltage	

201 - Common U.S. OEM Bill Of Materials

Suction Connection	Sweat
Suction Size	1 3/8"
Discharge Connection	Sweat
Discharge Size	7/8"
Electrical Connection	Terminal Block
Mounting Assembly	Available
Sight Glass	
Crankcase Heater	
Schrader Valve	
Tandem Ready	
Module Voltage	
Reference Drawing	

800 - Common U.S. Service Bill Of Materials

Suction Connection	Sweat
Suction Size	1 3/8"
Discharge Connection	Sweat
Discharge Size	7/8"
Electrical Connection	
Mounting Assembly	Not Available
Sight Glass	
Crankcase Heater	
Schrader Valve	
Tandem Ready	
Module Voltage	
Reference Drawing	

8R0 - Common U.S. Service Bill Of Materials

Suction Connection	Sweat
Suction Size	1 3/8"

Discharge Connection	Sweat
Discharge Size	7/8"
Electrical Connection	
Mounting Assembly	Not Available
Sight Glass	
Crankcase Heater	
Schrader Valve	
Tandem Ready	
Module Voltage	
Reference Drawing	

8S0 - Common U.S. Service Bill Of Materials

Suction Connection	Sweat
Suction Size	1 3/8"
Discharge Connection	Sweat
Discharge Size	7/8"
Electrical Connection	
Mounting Assembly	Not Available
Sight Glass	
Crankcase Heater	
Schrader Valve	
Tandem Ready	
Module Voltage	
Reference Drawing	

C00 - Common U.S. OEM Bill Of Materials

Suction Connection	Sweat
Suction Size	1 3/8"
Discharge Connection	Sweat
Discharge Size	7/8"
Electrical Connection	Terminal Block
Mounting Assembly	Available

Sight Glass	
Crankcase Heater	
Schrader Valve	
Tandem Ready	
Module Voltage	
Reference Drawing	497-1319-00_004.pdf

C01 - Common U.S. OEM Bill Of Materials

Suction Connection	Sweat
Suction Size	1 3/8"
Discharge Connection	Sweat
Discharge Size	7/8"
Electrical Connection	
Mounting Assembly	Not Available
Sight Glass	
Crankcase Heater	
Schrader Valve	
Tandem Ready	
Module Voltage	
Reference Drawing	

C40 - Common U.S. OEM Bill Of Materials

Suction Connection	Sweat
Suction Size	1 3/8"
Discharge Connection	Sweat
Discharge Size	7/8"
Electrical Connection	Terminal Block
Mounting Assembly	Available
Sight Glass	
Crankcase Heater	
Schrader Valve	
Tandem Ready	

Module Voltage

Reference Drawing	497-1319-00_004.pdf
-------------------	-------------------------------------

C57 - Common U.S. OEM Bill Of Materials

Suction Connection	Sweat
--------------------	-------

Suction Size	1 3/8"
--------------	--------

Discharge Connection	Sweat
----------------------	-------

Discharge Size	7/8"
----------------	------

Electrical Connection	Terminal Block
-----------------------	----------------

Mounting Assembly	Available
-------------------	-----------

Sight Glass

Crankcase Heater


Schrader Valve

Tandem Ready

Module Voltage

Reference Drawing

Drawing



NOTE:
 ALL TOLERANCES ARE $\pm 3/32$ EXCEPT
 INDUSTRY STANDARDS APPLY TO
 FITTINGS AND VALVES.

ECND06470	30	CHANGED DIMENSION WAS:17 & REMOVED ES SPECS	11-20-12	UCM	RM	
31-0907-049	29	REDRAWN; CHG FORMAT FOR PROJECT INC	11-23-07	MMB	CHK	RS
31-0289-036	0	RELEASED	01-19-89	EG		
ENG TITLE NO.	REV.NO.	REVISIONS	DATE	BY	CHKD	APP
CONFIDENTIALITY NOTICE THIS DRAWING AND INFORMATION CONTAINED HEREIN ARE THE EXCLUSIVE PROPERTY OF EMERSON CLIMATE TECHNOLOGIES, INC. AND SHALL BE RETURNED UPON DEMAND AND SHALL NOT BE REPRODUCED IN WHOLE OR IN PART TO ANYONE ELSE OR USED, WITHOUT THE WRITTEN CONSENT OF EMERSON CLIMATE TECHNOLOGIES, INC.						
7	MATERIAL SPECIFICATION		DRAWN BY MMB		SUPERSEDES DWG. NO. / REV. NO. 497-0184-00 / 28	
	N/A		DATE 11-23-07		SCALE 1:4	
TITLE			DRAWING NUMBER			SHEET 1 OF 1
REF DWG-COPE COMP ASSM			497-0184-00			DW 4