

ZP122KCE-TF5

HFC, R-410A, 60 Hz, 3 - Phase, 200/230 V , [Also Available with Variable Frequency Drives](#)

Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Copeland Representative for international availability.

Summary

Performance		
Evaporator Temp. (°F)	45.00	35
Condensing Temp. (°F)	130.00	120
Return Gas Temp. (°F)	65.00	55
Liquid Temp. (°F)	115.00	105
Capacity (BTU/hr)	124000	110500
Power (W):	11000	9700
Current (Amps):	30.9	28.3
EER(BTU/Wh):	11.3	11.4
Mass Flow (lbs/hr):	1800	1520
Sound Data @		
Sound Power (dBA):	76 Avg	81 Max
Vibration mils(peak-peak):	3.0 Avg	4.5 Max
Record Date:	2017-11-07	
Mechanical		
Displacement (in^3/Rev):	6.85	
Displacement (ft^3/Hr):		
Overall Length (in):	11.70	
Overall Width (in):	10.30	
Overall Height (in):	22.00	
Mounting Length (in):	7.50	
Mounting Width (in):	7.50	
Mounting Height (in):	22.70	

Suction Size (in),Type:	1 3 / 4 Rotalock
Discharge Size (in),Type:	1 1 / 4 Rotalock
Initial Oil Charge (oz):	85
Oil Recharge (oz):	81
Oil Type:	3MA
Net Weight (lbs):	107.6
Internal Free Volume (in^3):	440.0

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

Electrical

LRA High* (Amps):	240
LRA Low*(Amps):	
LRA Half Winding (Amps):	
MCC (Amps):	53
Max Operating Current (Amps):	40.50
RLA, MCC/1.4(use for contactor selection)(Amps):	37.9
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	34.0
RPM:	3500
Box IP :	21
UL File No:	SA2337
UL File Date:	2012-06-20
European Pressure Equipment Directive (PED):	
Fluid Group**:	FG 2
PS Low / High Side (BAR):	29.5 / 45.0
TS Min (°C):	-35 / -35
TS Max (°C):	50 / 150
Volume (L) :	1.2 / 7.2

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

**Fluid Group 1 comprises dangerous fluids defined as: Explosive, extremely flammable, high flammable, very toxic, toxic, oxidizing.

Fluid Group 2 is for non-dangerous fluids defined as: non-explosive, non-toxic, non-flammable.

Capacitors

Type	Part No	Low MFD	High MFD	Volts	User Description
No data available in table					
Alternate Applications					
Refrigerant	Voltage	Phase	Frequency	Application	
R-410A HFC	200/220	3	50	Air Conditioning	

Service Parts

Service Parts				
Reference	Component	Quantity	Description	Comment
99	527-0221-00	1	SPACER-MOUNTING ASSM	
99	529-0099-00	1	POWER CABLE-MOLDED PLUG	
99	910-0715-00	1	VALVE-OIL ADJUSTMENT 1/4FL X M9	
99	918-0043-00	1	HEATER-CRANKCASE	240V 70W WRAP AROUND
99	918-0043-01	1	HEATER-CRANKCASE	480V 70W WRAP AROUND
99	921-0227-00	1	CONNECTOR BLOCK KIT	
99	998-0010-00	1	SIGHTGLASS KIT	
99	998-0034-02	1	SERV ADAPTOR KIT 7/8 STUB	DISCHARGE SWEAT TO ROTALOCK
99	998-0034-03	1	ADAP KIT 11/8"SWT / 13/4 RL	SUCTION SWEAT TO ROTALOCK
99	998-0034-08	1	ADPTR 11/4-12 TO 7/8 ID	DISCHARGE ROTALOCK TO SWEAT

Accessories

Accessories		
Category	Part Number	Description
(1) Variable Frequency Drive	EVH-322048-R21BEN	Copeland EVH VFD , 15 HP, 230 VAC, 3Ø, 48A, With DC link Choke & Add on EMI filter, Removeable LCD Display, IP21, BACnet/Modbus

Category	Part Number	Description
(1) Variable Frequency Drive	EVH-322048-R21BDN	Copeland EVH VFD , 15 HP, 230 VAC, 3Ø, 48A, With DC link Choke (Standard EVH), Removeable LCD Display, IP21, BACnet/Modbus
(1) Variable Frequency Drive	EVH-322048-R54BDN	Copeland EVH VFD , 15 HP, 230 VAC, 3Ø, 48A, With DC link Choke (Standard EVH), Removeable LCD Display, IP54, BACnet/Modbus
(1) Variable Frequency Drive	EVH-322048-R54BDB	Copeland EVH VFD , 15 HP, 230 VAC, 3Ø, 48A, With DC link Choke (Standard EVH), Removeable LCD Display, IP54, BACnet/Modbus
(1) Variable Frequency Drive	EVH-322048-R54BEN	Copeland EVH VFD , 15.0 HP, 230 VAC, 3Ø, 48A, With DC link Choke & Add on EMI filter, Removeable LCD Display, IP54, BACnet/Modbus
(1) Variable Frequency Drive	EVH-322048-R21BDB	Copeland EVH VFD , 15.0 HP, 230 VAC, 3Ø, 48A, With DC link Choke (Standard EVH), Removeable LCD Display, IP21, BACnet/Modbus
(1) Variable Frequency Drive	EVM-322048-N20MFN	Copeland EVM VFD , HP, VAC, 3Ø, 48A, IP20, Modbus RTU Only
(1) Variable Frequency Drive	EVM-322048-N20MNN	Copeland EVM VFD , HP, VAC, 3Ø, 48A, IP20, Modbus RTU Only
(1) Variable Frequency Drive	EVM-322048-E20ENN	Copeland EVM VFD , 15.0 HP, 230 VAC, 3Ø, 48A, No EMI filter, No Choke (Standard EVM), Seven Segment Embedded Display, IP20, Ethernet/BACnet/Modbus
(1) Variable Frequency Drive	EVM-322048-E20EFN	Copeland EVM VFD , 15.0 HP, 230 VAC, 3Ø, 48A, With add on EMI filter, Seven Segment Embedded Display, IP20, Ethernet/BACnet/Modbus

Electrical Components

Electrical Components

Nomenclature

ZP122KCE-TF5
Family Series
Z: Scroll
Application Range
P: A/C - R-410A/B
Capacity

122K: Capacity Multiplier-1000

Model Variation

C: Model Variation

Oil Type

E: Polyol Ester

Motor Type

T: 3 Phase

Motor Protection

F: Internal Inherent Protection

Voltage

5: 60Hz (200/230-3) 50Hz (200/220-3)

Miscellaneous

Alternate Application				
Refrigerant	Freq	Phase	Voltage	Application
HFC R-410A	50	3 Ø	200/220 V	R1 AC
Nomenclature				
ZP122KCE-TF5				

Bill-of-Materials

ZP122KCE-TF5 - BILL OF MATERIALS	
155 - Common U.S. OEM Bill Of Materials	
Suction Connection	Stub
Suction Size	1 1/8"
Discharge Connection	Stub
Discharge Size	7/8"
Electrical Connection	Molded Plug
Mounting Assembly	Not Available
Sight Glass	
Crankcase Heater	
Schrader Valve	Available
Tandem Ready	

Module Voltage	
Reference Drawing	497-3096-00_004.pdf

165 - Common U.S. OEM Bill Of Materials

Suction Connection	Rotalock
Suction Size	1 3/4"
Discharge Connection	Rotalock
Discharge Size	1 1/4"
Electrical Connection	
Mounting Assembly	Not Available
Sight Glass	
Crankcase Heater	
Schrader Valve	
Tandem Ready	
Module Voltage	
Reference Drawing	497-1744-01_007.pdf

250 - Common U.S. OEM Bill Of Materials

Suction Connection	Stub
Suction Size	1 1/8"
Discharge Connection	Stub
Discharge Size	7/8"
Electrical Connection	Terminal Block
Mounting Assembly	Available
Sight Glass	
Crankcase Heater	
Schrader Valve	
Tandem Ready	
Module Voltage	
Reference Drawing	497-1744-02_007.pdf

265 - Common U.S. OEM Bill Of Materials

Suction Connection	Rotalock
--------------------	----------

Suction Size	1 3/4"
Discharge Connection	Rotalock
Discharge Size	1 1/4"
Electrical Connection	Terminal Block
Mounting Assembly	Available
Sight Glass	
Crankcase Heater	
Schrader Valve	
Tandem Ready	
Module Voltage	
Reference Drawing	497-1744-03_007.pdf

412 - Common U.S. OEM Bill Of Materials

Suction Connection	Stub
Suction Size	1 1/8"
Discharge Connection	Stub
Discharge Size	7/8"
Electrical Connection	
Mounting Assembly	Not Available
Sight Glass	
Crankcase Heater	
Schrader Valve	
Tandem Ready	
Module Voltage	
Reference Drawing	497-1744-05_007.pdf

414 - Common U.S. OEM Bill Of Materials

Suction Connection	Stub
Suction Size	1 1/8"
Discharge Connection	Stub
Discharge Size	7/8"
Electrical Connection	Terminal Block

Mounting Assembly	Not Available
Sight Glass	
Crankcase Heater	
Schrader Valve	Available
Tandem Ready	Yes
Module Voltage	
Reference Drawing	497-3096-03_003.pdf

415 - Common U.S. OEM Bill Of Materials

Suction Connection	Stub
Suction Size	1 1/8"
Discharge Connection	Stub
Discharge Size	7/8"
Electrical Connection	
Mounting Assembly	Not Available
Sight Glass	
Crankcase Heater	
Schrader Valve	
Tandem Ready	
Module Voltage	
Reference Drawing	497-1744-06_007.pdf

421 - Common U.S. OEM Bill Of Materials

Suction Connection	Stub
Suction Size	1 1/8"
Discharge Connection	Stub
Discharge Size	7/8"
Electrical Connection	Terminal Block
Mounting Assembly	Not Available
Sight Glass	
Crankcase Heater	
Schrader Valve	Available

Tandem Ready	Yes
Module Voltage	
Reference Drawing	497-3096-02_003.pdf

422 - Common U.S. OEM Bill Of Materials

Suction Connection	Stub
Suction Size	1 1/8"
Discharge Connection	Stub
Discharge Size	7/8"
Electrical Connection	
Mounting Assembly	Not Available
Sight Glass	
Crankcase Heater	
Schrader Valve	
Tandem Ready	
Module Voltage	
Reference Drawing	497-1744-08_007.pdf

423 - Common U.S. OEM Bill Of Materials

Suction Connection	Stub
Suction Size	1 1/8"
Discharge Connection	Stub
Discharge Size	7/8"
Electrical Connection	Terminal Block
Mounting Assembly	Not Available
Sight Glass	
Crankcase Heater	
Schrader Valve	
Tandem Ready	Yes
Module Voltage	
Reference Drawing	497-1328-00_006.pdf

424 - Common U.S. OEM Bill Of Materials

Suction Connection	Stub
Suction Size	1 1/8"
Discharge Connection	Stub
Discharge Size	7/8"
Electrical Connection	Terminal Block
Mounting Assembly	Not Available
Sight Glass	
Crankcase Heater	
Schrader Valve	
Tandem Ready	Yes
Module Voltage	
Reference Drawing	497-1328-00_006.pdf

425 - Common U.S. OEM Bill Of Materials

Suction Connection	Stub
Suction Size	1 1/8"
Discharge Connection	Stub
Discharge Size	7/8"
Electrical Connection	Terminal Block
Mounting Assembly	Not Available
Sight Glass	
Crankcase Heater	
Schrader Valve	Available
Tandem Ready	Yes
Module Voltage	
Reference Drawing	497-3096-04_003.pdf

449 - Common U.S. OEM Bill Of Materials

Suction Connection	Stub
Suction Size	1 1/8"
Discharge Connection	Stub
Discharge Size	7/8"

Electrical Connection	
Mounting Assembly	Not Available
Sight Glass	
Crankcase Heater	
Schrader Valve	
Tandem Ready	
Module Voltage	
Reference Drawing	

450 - Common U.S. OEM Bill Of Materials

Suction Connection	Stub
Suction Size	1 1/8"
Discharge Connection	Stub
Discharge Size	7/8"
Electrical Connection	Terminal Block
Mounting Assembly	Not Available
Sight Glass	
Crankcase Heater	
Schrader Valve	Available
Tandem Ready	Yes
Module Voltage	
Reference Drawing	497-3096-02_003.pdf

451 - Common U.S. OEM Bill Of Materials

Suction Connection	Stub
Suction Size	1 1/8"
Discharge Connection	Stub
Discharge Size	7/8"
Electrical Connection	
Mounting Assembly	Not Available
Sight Glass	
Crankcase Heater	

Schrader Valve	
Tandem Ready	
Module Voltage	
Reference Drawing	497-1744-04_007.pdf

455 - Common U.S. OEM Bill Of Materials

Suction Connection	Stub
Suction Size	1 1/8"
Discharge Connection	Stub
Discharge Size	7/8"
Electrical Connection	Terminal Block
Mounting Assembly	Available
Sight Glass	
Crankcase Heater	
Schrader Valve	Available
Tandem Ready	Yes
Module Voltage	
Reference Drawing	497-3096-00_004.pdf

457 - Common U.S. OEM Bill Of Materials

Suction Connection	Stub
Suction Size	1 1/8"
Discharge Connection	Stub
Discharge Size	7/8"
Electrical Connection	
Mounting Assembly	Not Available
Sight Glass	
Crankcase Heater	
Schrader Valve	
Tandem Ready	
Module Voltage	
Reference Drawing	497-1744-04_007.pdf

465 - Common U.S. OEM Bill Of Materials

Suction Connection	Rotalock
Suction Size	1 3/4"
Discharge Connection	Rotalock
Discharge Size	1 1/4"
Electrical Connection	Terminal Block
Mounting Assembly	Available
Sight Glass	
Crankcase Heater	
Schrader Valve	Available
Tandem Ready	Yes
Module Voltage	
Reference Drawing	497-3096-01_003.pdf

484 - Common U.S. OEM Bill Of Materials

Suction Connection	Stub
Suction Size	1 1/8"
Discharge Connection	Stub
Discharge Size	7/8"
Electrical Connection	Molded Plug
Mounting Assembly	Not Available
Sight Glass	
Crankcase Heater	
Schrader Valve	Available
Tandem Ready	Yes
Module Voltage	
Reference Drawing	497-3096-03_003.pdf

491 - Common U.S. OEM Bill Of Materials

Suction Connection	Stub
Suction Size	1 1/8"
Discharge Connection	Stub

Discharge Size	7/8"
Electrical Connection	Molded Plug
Mounting Assembly	Not Available
Sight Glass	
Crankcase Heater	
Schrader Valve	Available
Tandem Ready	Yes
Module Voltage	
Reference Drawing	497-3096-00_004.pdf

492 - Common U.S. OEM Bill Of Materials

Suction Connection	Stub
Suction Size	1 1/8"
Discharge Connection	Stub
Discharge Size	7/8"
Electrical Connection	Molded Plug
Mounting Assembly	Not Available
Sight Glass	
Crankcase Heater	
Schrader Valve	Available
Tandem Ready	Yes
Module Voltage	
Reference Drawing	497-3096-00_004.pdf

4C5 - Common U.S. OEM Bill Of Materials

Suction Connection	Stub
Suction Size	1 1/8"
Discharge Connection	Stub
Discharge Size	7/8"
Electrical Connection	Terminal Block
Mounting Assembly	Not Available
Sight Glass	

Crankcase Heater	
Schrader Valve	Available
Tandem Ready	Yes
Module Voltage	
Reference Drawing	497-3096-00_004.pdf

4U1 - Common U.S. OEM Bill Of Materials

Suction Connection	Stub
Suction Size	1 1/8"
Discharge Connection	Stub
Discharge Size	7/8"
Electrical Connection	Molded Plug
Mounting Assembly	Not Available
Sight Glass	
Crankcase Heater	
Schrader Valve	Available
Tandem Ready	Yes
Module Voltage	
Reference Drawing	497-3096-05_003.pdf

855 - Common U.S. Service Bill Of Materials

Suction Connection	Stub
Suction Size	1 1/8"
Discharge Connection	Stub
Discharge Size	7/8"
Electrical Connection	Molded Plug
Mounting Assembly	Not Available
Sight Glass	
Crankcase Heater	
Schrader Valve	Available
Tandem Ready	
Module Voltage	

Reference Drawing	497-3096-00_004.pdf
-------------------	-------------------------------------

884 - Common U.S. Service Bill Of Materials

Suction Connection	Stub
Suction Size	1 1/8"
Discharge Connection	Stub
Discharge Size	7/8"
Electrical Connection	Molded Plug
Mounting Assembly	Not Available
Sight Glass	
Crankcase Heater	
Schrader Valve	Available
Tandem Ready	Yes
Module Voltage	

Reference Drawing	497-1744-06_007.pdf
-------------------	-------------------------------------

8U1 - Common U.S. Service Bill Of Materials

Suction Connection	Stub
Suction Size	1 1/8"
Discharge Connection	Stub
Discharge Size	7/8"
Electrical Connection	Molded Plug
Mounting Assembly	Available
Sight Glass	
Crankcase Heater	
Schrader Valve	Available
Tandem Ready	Yes
Module Voltage	

Reference Drawing	497-3096-05_003.pdf
-------------------	-------------------------------------

8U5 - Common U.S. Service Bill Of Materials

Suction Connection	Stub
Suction Size	1 1/8"

Discharge Connection	Stub
Discharge Size	7/8"
Electrical Connection	Molded Plug
Mounting Assembly	Available
Sight Glass	
Crankcase Heater	
Schrader Valve	
Tandem Ready	Yes
Module Voltage	
Reference Drawing	497-3096-05_003.pdf

915 - Common U.S. Service Bill Of Materials

Suction Connection	Stub
Suction Size	1 1/8"
Discharge Connection	Stub
Discharge Size	7/8"
Electrical Connection	
Mounting Assembly	Not Available
Sight Glass	
Crankcase Heater	
Schrader Valve	
Tandem Ready	
Module Voltage	
Reference Drawing	497-1744-06_007.pdf


950 - Common U.S. Service Bill Of Materials

Suction Connection	Stub
Suction Size	1 1/8"
Discharge Connection	Stub
Discharge Size	7/8"
Electrical Connection	Terminal Block
Mounting Assembly	Available






Sight Glass	
Crankcase Heater	
Schrader Valve	Available
Tandem Ready	
Module Voltage	
Reference Drawing	497-3096-00_004.pdf

965 - Common U.S. Service Bill Of Materials

Suction Connection	Rotalock
Suction Size	1 3/4"
Discharge Connection	Rotalock
Discharge Size	1 1/4"
Electrical Connection	Terminal Block
Mounting Assembly	Available
Sight Glass	
Crankcase Heater	
Schrader Valve	Available
Tandem Ready	
Module Voltage	
Reference Drawing	497-1744-01_007.pdf



- NOTES:
- 1 ALL TOLERANCES ± 1.5 [0.06] UNLESS OTHERWISE SPECIFIED DUE TO ACCUMULATED ASSEMBLY TOLERANCES THE LISTED COMPONENTS MAY VARY FROM THE MOUNTING HOLES AS TABULATED.
 - 2 ALL FITTINGS: ± 3.0 [0.12]
 - 3 MOUNTING KIT.
 - 4 TUBE ENDS MUST BE PLUGGED.
 - 5 GROUNDING SCREW AND WASHER PER BOM.
 - 6 GAS EQUALIZATION FITTING FOR TANDEM READY ONLY



ECN307293	7	SEE SHEET 1	08-03-18	JXD	JL	KJ
ECN307189	6	REMOVED -05	03-23-18	TLD	JLS	KJ
ECN201315	5	ADDED SHEET 3 - VIEWS AND DIMS	09-13-16	KRB	LLB	KJR
ENG NOTICE NO.	REV.NO.	REVISIONS	DATE	BY	CHKD	APPR
CONFIDENTIALITY NOTICE						
0	THIS DRAWING AND INFORMATION CONTAINED HEREIN ARE THE EXCLUSIVE PROPERTY OF EMERSON CLIMATE TECHNOLOGIES, INC. AND SHALL BE RETURNED UPON DEMAND AND SHALL NOT BE REPRODUCED IN WHOLE OR IN PART. DISCLOSED TO ANYONE ELSE OR USED WITHOUT THE WRITTEN CONSENT OF EMERSON CLIMATE TECHNOLOGIES, INC.					
MATERIAL SPECIFICATION		DRAWN BY	SUPERSEDES DWG. NO. / REV. NO.			
N/A		JXD	497-1744-00/000			
		DATE	SCALE	DATE FORMAT:		
		10-22-14	0.35:1	MM-DD-YY		
TITLE			DRAWING NUMBER	SHEET 3 OF 3		
REF DWG-WELD COMP ASSM			497-1744-00	4		



EMERSON
Climate Technologies



Copeland
brand products

INTERPRET PER ASME Y14.5M-1994 AND EMERSON CLIMATE TECHNOLOGIES, INC. DESIGN STANDARDS DS2002

DO NOT SCALE DRAWING

CRITICAL PRODUCT CHARACTERISTICS

THIRD ANGLE PROJECTION

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE MILLIMETER OR (INCH)

TOLERANCES:

1-PLANE: N/A

2-FLANGE: N/A

3-ANGULAR: N/A